

Agitadores Mixers

SERIE AGV



Potencia Motor	Longitud Asta Inox	AGV1400 (4 Polos) Precio/Price	AGV 900 (6 Polos) Precio/Price
0.18 KW	60 cm	€ 852,84	€ 895,07
0.25 KW	60 cm	€ 895,07	€ 936,27
0.37 KW	80 cm	€ 936,27	€ 1061,93
0.55 KW	90 cm	€ 1041,33	€ 1145,36
0.75 KW	100 cm	€ 1165,96	€ 1353,42
1.1 KW	125 cm	€ 1540,88	€ 1602,68
1.5 KW	150 cm	€ 1707,74	€ 1873,57

Agitadores serie AGV / Mixers AGV Series

Agitador rápido con motor a 4-6-8 polos IP 55 equipado con soporte Radial y Anillo de sello. Particularmente usados para la mezcla de reactivos químicos o para disoluciones y la preparación de soluciones de baja viscosidad, en tanques de pequeño a mediano tamaño. Motor trifásico (opción Monofásico). Tipo de impulsor "hélice marina" inclinada a 35°. Material Aisi 304 (version standard) – AISI 316 +10%, eje e impulsor cubierto en PVC o Ebanite +20%, revestimiento PP +25%.

Swift mixers with rigid coupling by motors 4 – 6 – 8 poles equipped witha support Radial bearing and seal ring. This mixers are particularly suitable for mixing or dissolution of products with low viscosity In little – medium tanks. Maximum rating of Kw 5 white single or double staffing boxes Materials SS 304 (standard) - AISI 316 +10%, shaft and impeller sheathed in Rubber Ebanite or PVC +20%, shaft and impeller in PP covering a steel core +25%.

Motor monofásico (disponible hasta 0.37kW): +10%
 Single phase motor (available up to 0.37kW): +10%

SERIE AGR-V



Potencia Motor	Longitud Asta Inox	AGV 700 (8 Polos) Precio/Price	Longitud Asta Inox	RPM	AGR-V (4 Polos) Precio/Price
0.18 KW	-	-	70	140	€ 957,90
0.25 KW	80 cm	€ 1103,13	80	90	€ 1061,93
0.37 KW	80 cm	€ 1165,96	100	90	€ 1165,96
0.55 KW	100 cm	€ 1312,22	100	90	€ 1478,05
0.75 KW	100 cm	€ 1519,25	120	90	€ 1602,68
1.1 KW	120 cm	€ 2227,89	150	90	€ 1977,60
1.5 KW	150 cm	€ 2497,75	150	70	€ 2061,03

Agitadores serie AGR-V / Mixers AGR-V Series

Agitador lento directamente acoplado al eje del hueco de la rueda helicoidal. Son especialmente adecuados para tanques de Floculación, Neutralización o la preparación de soluciones de Polielectrolito, etc... Fijación por brida reductor. Impulsor con 4 hojas inclinadas a 45 grados. Motor Trifásico (opción Monofásico). Material AISI 304 (version standard)- AISI 316 + 10%, eje e impulsor cubierto en PVC o Ebanite +20% revestimiento PP +25%.

Slow mixers are used in water treatment plants . (In small tanks max 5000 Lit). The shaft of the mixer is directly key coupled with the hollow of the Worm gear box, supplied with shaft and impeller 4 blades 45°. AISI 316 +10%, shaft and impeller sheathed in Rubber Ebanite - PVC +20%, shaft and impeller in PP covering a steel core +25%

Motor monofásico (disponible hasta 0.37kW): +10%
 Single phase motor (available up to 0.37kW): +10%

SERIE AF



Código Part. No.	Tipo	Potencia Motore	Longitud Albero	Aliment. Eléctrica (4 Polos)	Precio
AGT 1241 003	PP AF 1-6-4	0.18 KW	600 mm	230/400 V - 50 Hz 3 Phase	€ 437,75
AGT 1242 003	PP AF 1-6-4	0.18 KW	600 mm	230 V - 50 Hz 1 Phase	€ 437,75
AGT 1241 103	PP AF 2-8-4	0.18 KW	800 mm	230/400 V - 50 Hz 3 Phase	€ 437,75
AGT 1242 103	PP AF 2-8-4	0.18 KW	800 mm	230 V - 50 Hz 1 Phase	€ 437,75
AGT 1241 001	SS316 AF1-6-4	0.18 KW	600 mm	230/400 V - 50 Hz 3 Phase	€ 545,90
AGT 1242 001	SS316 AF1-6-4	0.18 KW	600 mm	230 V - 50 Hz 1 Phase	€ 545,90
AGT 1241 101	SS316 AF2-8-4	0.18 KW	800 mm	230/400 V - 50 Hz 3 Phase	€ 545,90
AGT 1242 101	SS316 AF2-8-4	0.18 KW	800 mm	230 V - 50 Hz 1 Phase	€ 545,90

Agitadores serie AF / Mixers AF Series

Agitador rápido para depósitos pequeños (max 200 lt). Motor de 4 polos 1400gir/min. Eje e impulsor en Acero inoxidable 316 o completamente revestido en PP. Brida en PP. Eje tipo " hélice marina " .

Motor driven high speed mixers for small tanks (200 lt) capacity, with shaft bearings sealed by a "V" ring ing to protect from external vapours. Motor 4 pole, 1400 rpm. Mixer support flange made of PP mounted directly on the tank. Shaft and impeller in stainless steel 316 or PP covering a steel core. Impeller flow cone type.

Formación Código - Code

